

HYDRAL 6 (UL) Foam Concentrate

Premium performance Aqueous Film-Forming Foam (AFFF) concentrate at 6% for hydrocarbon fires

Description

HYDRAL 6 (UL) is an aqueous film forming foam concentrates (AFFF) based on fluorosurfactants, hydrocarbon tensides and glycol ethers for use at 6% induction ratio.

AFFF is a synthetic concentrate comprised of detergent and fluorocarbon surfactant that form foam with the inherent ability to produce a vapour suppressing aqueous film on the surface of the hydrocarbon fuels.

Performance

HYDRAL 6 (UL) is measured against highest specifications and standards such as the latest edition of the UL-162 standard.

AFFF provides a rapid flame knock down on class B fires involving hydrocarbon fuels such as oil, petroleum and aviation fuels.

On application, the foam spreads rapidly to form an aqueous film and foam blanket. The aqueous film suppresses the release of fuel vapours. The foam blanket effectively excludes oxygen from the fuel surface, extinguishing the fire and preventing re-ignition.

Additionally it provides a cooling function on the fuel by enclosed water and makes the water float on fuel surfaces in spite of it's usually higher density.

HYDRAL 6 (UL) can be used by most conventional foam equipment such as:

- Balance pressure pump proportioning equipment
- Bladder tank and related proportioners
- Around-the-pump proportioners
- Fixed and portable In-line venturi type inductors
- Fixed or handline nozzles with fixed induction/pick up tubes



Application

HYDRAL 6 (UL) is ideal for sprinkler systems, process plants, pumping stations, aircraft hangars and tank protection and non-air-aspirating handline nozzles.

The foam produced by HYDRAL 6 (UL) extinguishes hydrocarbon fires by either forceful or gentle application.

HYDRAL 6 (UL) is compatible with all foam-compatible dry chemical extinguishing powders.

Sea water can be used without an increase in the application rate.

Approvals

HYDRAL 6 (UL) is approved or listed according to:

- UL-162 Listed



Storage and Shelf Life

HYDRAL 6 (UL) has an operational temperature range of -20°C and +60°C. Limited exposure to temperatures above +60°C does not affect the firefighting performance.

When stored in the packaging supplied (polyethylene drums or cans) or in equipment recommended by the manufacturer as part of the foam system and within the temperature limits specified, the shelf life of HYDRAL 6 (UL) Concentrate is about 20-25 years.

The factors affecting shelf life and stability for SABOFOAM agents are discussed in detail in our Technical Bulletin for storage recommendation.

If the product is frozen during storage or transportation, the concentrate should be thawed and used without any degeneration of the performance.

Safety and handling

See our corresponding "Material Safety data sheet".

Materials of Constructions Compatibility

Tests have been performed with HYDRAL Concentrate verifying its compatibility with standard carbon steel "black" pipe and pipe manufactured from various stainless steel or brass compounds.

Alternative pipe, fittings, and valves may be used in some cases if acceptable to the customer and/or the authority having jurisdiction.

Refer to our Technical Bulletin, addressing acceptable materials of construction for use with SABOFOAM concentrates.

Galvanized pipe and fittings must not be used in areas where undiluted concentrate will contact them since corrosion will result.

Please first consult Tyco for specific guidelines concerning materials of construction. For more specific information regarding, please email at: sabofoam.levate@tycoint.com

Quality Assurance

HYDRAL 6 (UL) – as with all TYCO Products – is subject to very stringent quality controls throughout all stages of production, from incoming raw to the complete product and is manufactured in an ISO 9001:2008 controlled facility. Quality assurance is therefore guaranteed.

Typical Properties

■ HYDRAL 6 (UL)	AFFF 6%
■ Fire Classes	A and B
■ Shape and colour	Pale yellow clear liquid
■ Smell	Characteristic, surfactant-alike
■ Density (20°C)	1.02 ±0.02 [g/ml]
■ pH (concentrate, 20°C)	7.5 ±0.5
■ Viscosity 20°C	3.0 ±1.0 [mm ² /s]
■ Sediment (EN 1568)	≤ 0.1 [%]
■ Admixing ratio	6 [% Vol.]
■ Expansion Ratio (EN 1568-3)	≥ 8.0
■ Drain Time 25%, (20°C, EN 1568-3)	≥ 2:30 [min:s]
■ Drain Time 50%, (20°C, EN 1568-3)	≥ 4:00 [min:s]
■ Expansion	Low, (Medium)
■ Freezing Point	≤ -20 [%]
■ Pour Point	≤ -18 [%]
■ Recommended storage/ Usage temperature	-15 to +60 [°C]

Ordering Information

HYDRAL 6 EX can be supplied in cans, drums, totes or Bulk (contact us for Bulk delivery).

<u>Part No.</u>	<u>Description</u>
■ F106309C1	25 Litre drum
■ F106309D1	200 Litre drum
■ F106309T1	1000 Litre tote
■ F106309B1	Bulk

www.sabofoam.com